TECHNICAL PARAMETERS FOR SOLID FUEL LOCAL SPACE HEATERS EU 2015/1185 OF 24. APRIL 2015

Model identifier(s): Scan 1006 Vermiculite	
Indirect heating functionality	No
Direct heat output(kW)	7
Indirect heat output(kW)	N.A
	Emissions from space heating at nominal heat output

						at nominal heat output		
				Preferred fuel Model		PM (OGC CO	NO _x
Fuel				(Only one)	identifier(s)	[X] mg/Nm	$n_3 (13\% 0_2)$	
Wood logs with moisture of	content ← 25	5%		Yes	No	20 6	52 968	95
Compressed wood with m	oisture cont	ent < 12%		No	No			
Other woody biomass				No	No			
Anthracite and dry steam coal				No	No			
Hard coke				No	No			
Low temperature coke				No	No			
Bituminous coal				No	No			
Lignite briquettes				No	No			
Peat briquettes				No	No			
Blended fossil fuel briquettes				No	No			
Other fossil fuel				No	No			
Blended biomass and fossil fuel briquettes				No	No			
Other blend of biomass and solid fuel			No	No				
Characteristics when op	erat <u>ing with</u>	the prefer	red fuel					
Seasonal space heating er				-				
Energy Efficiency Class				A+				
Energy Efficiency Index (EEI)			109					
ltem	Symbol	Value	Unit	I	tem	Symbol	Value	Unit
Heat output					ency (NCV as re			
Nominal heat output	P _{nom}	7	kW	Useful efficiency at nominal heat output		$\eta_{\rm th,nom}$	82	%
Minimum heat output (indicative)	P _{min}	N.A.	kW	Useful effic minimum he output (ind	eat	$\eta_{_{th,min}}$	N.A.	%
Auxiliary electricity con	sumption			Type of he	at output/roo	m tempera	ture contro	(select one
At nominal heat output	el _{max}	x,xxx	kW	single stage heat output, no room temperature control			[yes/no]	
At minimum heat output	el _{min}	x,xxx	kW	two or more manual stages, no room temperature control			[yes/no]	Yes
In standby mode	el _{sB}	x,xxx	kW	with mechanic thermostat room temperature control			[yes/no]	
				with electronic room temperature control			[yes/no]	
				with electronic room temperature control plus day timer			[yes/no]	
					with electronic room temperature control plus week timer		[yes/no]	
				Other cont	Other control options (multiple s			e)
				room temp presence d	room temperature control, with presence detection		[yes/no]	
				room temp open windo	room temperature control, with open window detection		[yes/no]	
				with distan	vith distance control option		[yes/no]	
Permanent pilot flame p	owe <u>r reauir</u>	eme <u>nt</u>						
Pilot flame power requirement (if applicable)	P _{pilot}	N.A.	kW			//	7	
Contact details	Name and a	address of t	he supplier:		Brian Ørun, R&E	Manager, Scan	A/S, Denmark	

/